



## Description

Style 2300 packing is an Expanded PTFE braided packing. This dense and resilient product has the ability to withstand extreme chemical attack. The high tensile strength of this product, together with resistance to hardening, has proven that it will consistently outlast the valve it was installed in, when used in block valves. Furthermore, the materials used in this product comply with the FDA requirements set out for minimal food contact as well as incidental food contact.

## Construction

Style 2300 is a braided packing constructed of Expanded PTFE yarns which have been inter-braided into a dense, but flexible product. There are no lubricants that can migrate out of this product.

## Application

Style 2300 is ideally suited for both pump and valve applications. PTFE has become the industry standard for harsh Acidic or Alkaline applications due to the ability to withstand the attack. Style 2300 has the advantage that it is non-contaminating and as such can also be used in applications where there is sensitivity to product contamination. This product is typically used in Medical, Petrochemical, Oxygen and Food production.

### Size & Weight - Style 2300 Packing

mm	3	4	5	6	7	8	10	11	12	13
inch	1/8	5/32	3/16	1/4	-	5/16	3/8	7/16	1/2	-
m/kg	75	44	28.1	19.5	15	11	6.5	5.6	4.5	4

mm	14	15	16	18	19	20	22	24	25	-
Inch	9/16	-	5/8	11/16	3/4	13/16	7/8	15/16	1	-
m/kg	3.5	3	2.5	2	1.8	1.6	1.4	1.3	1.2	-

### Specification

Item	UoM	Magnitude	
		Dimensional Deviation	mm
		Radial	0.00 ~ -0.50
Working Temperature	°C	-200 ~ +280	
Pressure	bar	Rotary (Pumps)	15
		Stationary (Valves)	150
Surface Speed	m/sec	8	
pH	pH	0 - 14	
Base Yarn	-	Expanded PTFE Yarn	
Lubrication	-	Zero	