



Description

Style 4600 packing is a non-Asbestos twisted rope packing that has been formulated especially for the replacement of Asbestos. Style 4600 packing is designed specifically for use on stationary applications where a square braided product is not required, typically as an insulation material.

Construction

Style 4600 is a twisted rope packing, constructed of a pure Blown Glass Fibre. There are no wet lubricants present that can be extruded under pressure and temperature.

Application

The safety aspect of a non-Asbestos packing makes this an ideal insulation product. This product is for use in both high and low temperature applications.

Size & Weight - Style 4600 Packing

mm	5	6	8	10	12	15	18	25	30	40
inch	3/16	1/4	5/16	3/8	1/2	-	11/16	1	1 1/8	1 1/2
m/kg	16	22	40	60	80	150	200	350	500	850
mm	50	-	-	-	-	-	-	-	-	-
Inch	2	-	-	-	-	-	-	-	-	-
m/kg	1200	-	-	-	-	-	-	-	-	-

Specification

Item	UoM	Magnitude	
Dimensional Deviation	mm	Axial	0.00 ~ +1.00
		Radial	0.00 ~ -1.00
Working Temperature	°C	+/- 500	
Pressure	bar	Stationary (Valves)	N/A
Surface Speed	m/sec	1	
pH	pH	3 - 14	
Base Yarn	-	Glass Fibre	
Lubrication	-	N/A	